

2900 Barrel



Serie **P**
Pneumatic airless piston pump

2900 Barrel

RUST PROOFING SPRAYING EQUIPMENT

The pneumatic transfer pump 2900 BARREL has been built after an experience of over 35 years of Taiver in the field! It is ideal for pumping and transferring self-level liquids and materials, inks, oils, cataphoresis baths, intumescent products and any product with a viscosity up to 100.000 centipoises.

Performances:

- Available in two versions:
 - * For 200 ltr drums
 - * For 60 ltr drums
 - * For 20 ltr drums
- High performance Rust Proofing system
- Tungsten carbide valves
- Pumping housing in stainless steel for the maximum quality.
- Ideal for transferring inks
- Particularly suitable for intumescent products in the mechanical industry
- Packing are spring loaded
- No air lubrication required
- No freezing of air motor
- Affordable pricing

Target Coatings:

- Rustproofing coatings
- Oils
- Greases

Technical Data:

Motor		Pneumatic
Ratio		15:1
Max. Free Flow Delivery	ltr/min	8
Max. Working Pressure (bar)		110
Weight	kg.	10
Air Consumption	ltr/min	250-400
Max. suggested Viscosity (Centipoise)		2.000

Construction specifications:

2900 BARREL uses an avant-garde technology which includes two patents: The instant volumetric reversal of pneumatic motor, that means a very low pressure drop during the reversal, and the simultaneous adjustment of packings. This simultaneous adjustment, depending on the wear, allows a longer life and a better performance of the unit. The piston is hard chrome treated and all the parts in contact with the products are in stainless steel. Very easy maintenance. Tungsten carbide valves.

