

# 3200 PLUS



Serie **P**  
Pneumatic airless piston pump

# 3200 PLUS

3200 PLUS is an airless pneumatic pump especially used in the small industry and handicrafts.

3200 PLUS is ideal for spraying lakes, paints, polyurethans, for furniture polishing.

This airless pneumatic pump works with a pneumatic motor which doesn't need any lubrication and has no ice problems.

The instant volumetric reversal of the motor allows a constant flow without pulsations.

## Construction specifications:

3200 PLUS uses an avant-garde technology: The pneumatic motor, instant volumetric reversal works without lubrication and has no ice problems. The pump cylinder has a special hardening treatment, which allows a longer life of pumps. Adjustable upper packing, tungsten carbide valves.

## Performances:

3200 PLUS with a ratio 26:1 and a delivery of 18 cm<sup>3</sup> per cycle. The air motor, instant volumetric reversal (Taiver patented) allows a constant atomizing pressure and a high quality finishing. Light and handy to use, 3200 PLUS has no ice problems and the air motor can work in every place without lubrication.

## Available Set-up:

- Airless
- Air-mix
- 
- On Stand
- Trolley
- Wall Bracket

## Target Coatings:

|   |   |
|---|---|
| Lacquer / varnish / enamel (low visc)           | ■ |
| Primer / latex / enamel (med. visc)             | ■ |
| 2 component (med. visc.)                        | ■ |
| Low solvent & solvent free coatings (high visc) | ■ |
| Insulation and high build coatings              | ■ |
| Fire-proofing coatings                          | ■ |
| Water-proofing coatings / bituminous coatings   | ■ |
| Plasters / ready-mix gyps                       | ■ |
| Powder glass coatings                           | ■ |

## Technical Data:

|   |                   |
|---|-------------------|
| Pneumatic motor instant volumetric reversal | si                |
| Ratio                                       | 26:1              |
| Max. Free Flow Delivery                     | ltr/min 3,2       |
|   | 1 Gun 0,021       |
| Max. Spray Tip                              | 2 Guns 0,013      |
|   | 3 Guns ---        |
| Max. Working Pressure (bar)                 | 180               |
| Weight                                      | kg. 14            |
| Air consumption                             | ltr/min 250 - 400 |
| Max. suggested Viscosity (Centipoise)       | 160               |
| Packing type:                               | Mobile            |

