

GOLD 22000



Serie **GOLD**
Electric airless diaphragm pump

GOLD 22000

The airless system allows a high working speed and reduces the overspray, therefore paint and solvent saving. Less overspray means also less pollution and benefits for the worker's health!

GOLD 22000 is the ideal pump for big contractors who have to do very important and high productivity works. This renewed self-contained double diaphragm pump supplies an excellent performance using very low power (only 2 Kw). At present GOLD 22000 is the most powerful airless diaphragm pump on the market! It can spray thick and thixotropic products, two material components using a 1 :1 mixture, or using two or more guns simultaneously. This pump is ideal for big works in building, big carpentry, for waterproof jobs and in the naval field.

Construction specifications:

The electric motor GOLD 22000 is H class, that means: maximum quality and safety. It can work in very bad conditions and with very high temperature. An automatic system stops the pump when exceeding the electric safety limits. The head blocks are in stainless steel, the valves in tungsten carbide. GOLD 22000 has been designed for an easy maintenance.

Technical Data:

Volt	230 Volt	380 Volt	HONDA
	50 Hz	50 Hz	
Power	3 HP	3 HP	13 HP
Mixing Ratio:	1:1	1:1	1:1
Max. Free Flow Delivery	ltr/min 18	18	18
Max. Delivery with tip	ltr/min 11	11	11
	1 Gun 0,053	0,053	0,053
Max. Spray Tip	2 Guns 0,026	0,026	0,026
	3 Guns 0,021	0,021	0,021
Max. Working Pressure (bar)	220	220	280
Max. length HP hose mt.	100	100	100
Max. length HP hose (elevation) mt.	100	100	100
Weight	kg. 72	72	76
Max. suggested Viscosity (Centipoise)	600	600	600

Target Coatings:

Lacquer / varnish / enamel (low visc)	■
Primer / latex / enamel (med. visc)	■
2 component (med. visc.)	■
Low solvent & solvent free coatings (high visc)	■
Insulation and high build coatings	■
Fire-proofing coatings	■
Water-proofing coatings / bituminous coatings	■
Plasters / ready-mix gyphs	■
Resins / Injection's coatings	■

