

W MIX 3

HIGH PRESSURE AIR ASSISTED GUN



W MIX 5

HIGH PRESSURE AIR ASSISTED AUTOMATIC GUN



W.I.T. srl

Registered Office: P.le P.ssa Clotilde, 6 | 20121 Milan (MI) | Italy
Headquarter: Via Libero Grassi, 7 | 23875 Osnago (LC) | Italy
Tel +39 (0)39 514180 | Fax +39 (0)39 9515471 | info@witsrl.com |
www.witsrl.com VAT #: IT08003560961 | Reg. Imprese Milano: 1996552



IT'S EASY

W MIX 3 is the most versatile gun on the market, in fact it is compatible with the air-cap and air nozzles of the most important brands on the market.

The W MIX 3 is compatible with:



TECHNICAL DATA

Maximum Working Fluid Pressure	200 bar, 20 MPa (2900 psi)
Maximum Working Air Pressure	7 bar, 0,7 MPa (100 psi)
Maximum Working Fluid Temperature	43 °C
Fluid Inlet	¼" nps
Air Inlet	¼" nps
Gun Weight with filter holder	520 gr.
Gun Body	Forged Aluminum
Trigger Resistance	17.35 N
Wetted Parts	Stainless Steel, Carbide, PTFE.

The new air-assisted airless gun W MIX 3 is the perfect combination of precision, lightness, durability and handling. With its anatomical shape ensures all comfort to the user for a quality finishing.

Different use ... same result. W MIX 3 is also available in the version with self-cleaning nozzle.



TECHNICAL DATA

Maximum Working Fluid Pressure	200 bar, 20 MPa (2900 psi)
Maximum Working Air Pressure	7 bar, 0,7 MPa (100 psi)
Maximum Working Fluid Temperature	43 °C
Fluid Inlet	¼" nps
Air Inlet	¼" nps
Gun Weight with filter holder	520 gr.
Gun Body	Forged Aluminum
Trigger Resistance	17.35 N
Wetted Parts	Stainless Steel, Carbide, PTFE.



*The W MIX 5 as the W MIX 5, is compatible with the air cap and nozzles of the most important brands on the market.
The W MIX 5 is compatible with:*



The new air-assisted airless gun W MIX 5 offers a superior finishing quality. Light and precise, is completely in stainless steel to guarantee perfect quality during time.

TECHNICAL DATA

Maximum Working Fluid Pressure	200 bar, 20 MPa (2900 psi)
Maximum Working Air Pressure	7 bar, 0,7 MPa (100 psi)
Maximum Working Fluid Temperature	43 °C
Fluid Inlet	¼" nps
Air Inlet	¼" nps
Gun Weight	980 gr.
Gun Body	Stainless steel
Wetted Parts	Stainless Steel, Carbide, PTFE.
Lenght	118 mm
Width	45 mm
Height	72 mm

NOZZLES MEASURES



TT1

Cod.	Spray	Hole diam.	
	Angle	0.000"	mm
TTU207	20°	0.007	0:18
TTU307	30°	0.007	0:18
TTU407	40°	0.007	0:18
TTU507	50°	0.007	0:18
TTU607	60°	0.007	0:18
TTU209	20°	0.009	0:23
TTU309	30°	0.009	0:23
TTU409	40°	0.009	0:23
TTU509	50°	0.009	0:23
TTU609	60°	0.009	0:23
TTU211	20°	0.011	0:28
TTU311	30°	0.011	0:28
TTU411	40°	0.011	0:28
TTU511	50°	0.011	0:28
TTU611	60°	0.011	0:28
TTU213	20°	0.013	0:33
TTU313	30°	0.013	0:33
TTU413	40°	0.013	0:33
TTU513	50°	0.013	0:33
TTU613	60°	0.013	0:33
TTU215	20°	0.015	0:38
TTU315	30°	0.015	0:38
TTU415	40°	0.015	0:38
TTU515	50°	0.015	0:38
TTU615	60°	0.015	0:38
TTU217	20°	0.017	0:43
TTU317	30°	0.017	0:43
TTU417	40°	0.017	0:43
TTU517	50°	0.017	0:43
TTU617	60°	0.017	0:43



69UXXX

Cod.	Spray	Hole diam.
	Angle	0.000"
69U108	10°	0.008
69U208	20°	0.008
69U308	30°	0.008
69U408	40°	0.008
69U110	10°	0.010
69U210	20°	0.010
69U310	30°	0.010
69U410	40°	0.010
69U510	50°	0.010
69U112	10°	0.012
69U212	20°	0.012
69U312	30°	0.012
69U412	40°	0.012
69U512	50°	0.012
69U612	60°	0.012
69U114	10°	0.014
F69U214	20°	0.014
69U314	30°	0.014
69U414	40°	0.014
69U514	50°	0.014
69U614	60°	0.014
69U516	50°	0.016
69U616	60°	0.016
69U518	50°	0.018
69U618	60°	0.018
69U620	60°	0.020

SECTORS RECOMMENDED



FINISHING



METALS



INDUSTRY

Two-component, solvent, water-based materials, paint, lacquers, polyurethane or water-based glues. The W MIX serie is perfectly suited to all kinds of products.



W MIX 3

HIGH PRESSURE AIR ASSISTED GUN



W MIX 5

HIGH PRESSURE AIR ASSISTED AUTOMATIC GUN

W.I.T. srl

Registered Office: P.le P.ssa Clotilde, 6 | 20121 Milan (MI) | Italy

Headquarter: Via Libero Grassi, 7 | 23875 Osnago (LC) | Italy

Tel +39 (0)39 514180 | Fax +39 (0)39 9515471 | info@witsrl.com |

www.witsrl.com VAT #: IT08003560961 | Reg. Imprese Milano: 1996552

